

T8

Ballast Compatible™



FEATURES

- You can directly install Hyperikon's Ballast Compatible™ T8 LED tube.
- Working temperature: - 4 °F ~ 104 °F.
- Dimmable.
- Works with all ballast for T8.
- 5 years unlimited warranty.
- Double ended.
- Hyperikon's Ballast Compatible™ tubes work both with AND without ballast.

Hyperikon proudly presents the Ballast Compatible™ LED Tubes - the most hassle free existing LED tube. As the only one on the market, Hyperikon offers a product that works with AND without ballast. No rewiring and no technical skills required. Simply plug it in and experience the increased light quality and savings.

SPECIFICATIONS

*Customization available from Hyperikon factory on select orders

Model	Wattage (W)	Input (AC)	CCT	Lumen	CRI	Cover	Beam angle	Efficiency	Base
841000741BC	18 W	100-277 V	4000 K	2100 LM ± 5%	>82	Clear	>140°	117 LM/W	>140°
842000741BC	18 W	100-277 V	4000 K	2030 LM ± 5%	>82	Frosted	>140°	113 LM/W	>140°
841000751BC	18 W	100-277 V	5000 K	2200 LM ± 5%	>82	Clear	>140°	122 LM/W	>140°
842000751BC	18 W	100-277 V	5000 K	2130 LM ± 5%	>82	Frosted	>140°	118 LM/W	>140°

All Hyperikon products maintain all of the necessary certifications, including:

