



BR30 BULBS

PREMIUM LED LIGHTING SERIES
by Hyperikon®



E26 Base



Voltage
120 V



Dimmable



Lifespan
45,000+ Hrs



5 Year
Warranty



CRI
90+



Beam Angle
110°



UV free
Mercury free



Damp location
suitable

- Operating temperature of -22°F to 130°F
- Wide 110° beam angle which creates a smooth ambient environment
- 45,000+ hours of lifespan, more than 26 years based on 5Hrs/day average
- Device complies with Part 15 of the FCC Rules
- Device has been tested and found to comply with the limits for a class B digital device

HYPERIKON®

(888) 846-4973

info@hyperikon.com

9393 Waples St, Suite 120
San Diego, CA 92121

www.hyperikon.com

HYPERIKON®

A preferred choice by homeowners. Hyperikon® proudly presents our wonderful Hyperikon® LED BR30 bulb fitting any and all residential needs. Our BR30s are tailored to exceed your expectations when it comes to ambiance and color reflection performance. The bulb can be ordered in BR40-edition as well. Hyperikon® is proud of its premium BR-Series of LED Bulbs, setting the standard for excellence in LED downlight.



SPECIFICATIONS

Series	Hyperikon Code	Model Name	Wattage	Kelvin	Lumens	Voltage	CRI	Angle Beam	Base
BR30	302000401	HyperBR30-272	9W	2700K	700Lm	120V	90+	110°	E26
BR30	302000402	HyperBR30-302	9W	3000K	720Lm	120V	90+	110°	E26
BR30	302000403	HyperBR30-402	9W	4000K	740Lm	120V	90+	110°	E26
BR30	302000404	HyperBR30-502	9W	5000K	760Lm	120V	90+	110°	E26
BR30	302010401	HyperBR30-273	12W	2700K	900Lm	120V	90+	110°	E26
BR30	302010402	HyperBR30-303	12W	3000K	920Lm	120V	90+	110°	E26
BR30	302010403	HyperBR30-403	12W	4000K	940Lm	120V	90+	110°	E26
BR30	302010404	HyperBR30-503	12W	5000K	960Lm	120V	90+	110°	E26



MODEL DESIGN



WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock – do not use where directly exposed to water or weather.
- Suitable for damp locations outside as well as inside.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

