



BR40 BULBS

PREMIUM LED LIGHTING SERIES

by Hyperikon®



E26 Base



Voltage
120 V



Dimmable



Lifespan
45,000+ Hrs



5 Year
Warranty



CRI
90+



Beam Angle
110°



UV free
Mercury free



Damp location
suitable

- Operating temperature of -22°F to 130°F
- Wide 120° angle which creates a smooth ambient environment
- 45,000+ hours of lifespan, more than 26 years based on 5Hrs/day average
- Device complies with Part 15 of the FCC Rules
- Device has been tested and found to comply with the limits for a class B digital device

HYPERIKON®

(888) 846-4973

info@hyperikon.com

9393 Waples St, Suite 120
San Diego, CA 92121

www.hyperikon.com

HYPERIKON®

The Hyperikon® BR series provide similar or better output, light quality and beam profile characteristics than regular bulbs while consuming only a fraction of the power. These lamps blend seamlessly into the ceiling, provide smooth, highly diffused light, and are perfectly designed for recessed cans or track lighting. Available as ENERGY STAR® qualified, dimmable, and last more than 45,000 hours. The BR40 bulbs are easy to install, ideal for indoor and outdoor fixtures. They are UL Listed, and have FCC and RoHS certifications. They run cool with minimal heat output and have a high efficacy (more lumens per watt).



SPECIFICATIONS

Series	Hyperikon Code	Model Name	Wattage	Kelvin	Lumens	Voltage	CRI	Angle Beam	Base
BR40	402000401	HyperBR40-272	15W	2700K	1300Lm	120V	90+	110°	E26
BR40	402000402	HyperBR40-302	15W	3000K	1320Lm	120V	90+	110°	E26
BR40	402000403	HyperBR40-402	15W	4000K	1340Lm	120V	90+	110°	E26
BR40	402000404	HyperBR40-502	15W	5000K	1360Lm	120V	90+	110°	E26



MODEL DESIGN



WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather.
- Suitable for damp locations outside as well as inside.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

