



## LED WALL PACK

by Hyperikon®



CRI  
85+



Voltage  
120-277V



Dimmable



Lifespan  
45,000+ Hrs



5 Year  
Warranty



Efficacy  
82-100lm/w



Beam Angle  
90°



UV free  
Mercury free



Damp location  
suitable

- Device complies with Part 15 of the FCC Rules
- Sealed die-casting profile for outdoor applications
- Polycarbonate optical lens with UV stabilizers
- Built-in UL class 2 driver, optional for photocell
- UL/cUL listed and DLC qualified

**HYPERIKON®**

(888) 846-4973

info@hyperikon.com

9393 Waples St, Suite 120

San Diego, CA 92121

www.hyperikon.com

**HYPERIKON®**

These products are suitable for big spaces such as arenas or any type of closed off spaces that need a lot of light. They produce up to 12000 lumens depending on the wattage. These lights are a perfect solution for your exteriors. They operate with a large angle beam, much more than any other product on the market.



### SPECIFICATIONS

Hyperikon Code	Model Name	Wattage	Kelvin	Lumens	Voltage	CRI	Angle Beam	Base
552001001	HyperWall45-50	45 W	5000 K	3900 Lm	120-277 V	85+	90°	Mounted
552001002	HyperWall70-50	70 W	5000 K	6000 Lm	120-277 V	85+	90°	Mounted
552001003	HyperWall90-50	90 W	5000 K	7800 Lm	120-277 V	85+	90°	Mounted
552001004	HyperWall135-50	135 W	5000 K	12000 Lm	120-277 V	85+	90°	Mounted



### DIMENSIONS



### ACCESSORIES

A complimentary die cast aluminum housing is included. The "Dark Sky" approved metal hood features a high-quality, shatter-resistant epoxy lens, designed to withstand damaging effects of outdoor environments.



### WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather.
- Suitable for damp locations outside as well as inside.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

