

LED Retrofit Trim Downlight

Product Features


- Dimmable to 10% with select dimmers.
- Meets CEC's California Qualified Spec.
- Anti-Glared design with Baffle.
- High Output Bright LEDs.
- Instant On to Full Brightness.
- Suitable for wet locations.

Housing Compatability

- Suitable for type IC, type Non-IC and Air Tight Housings




Technical Characteristics



Average beam angle
(50%):100°

Dimensions And Weight

Model No.	L Length	D Diameter	Weight(g)	Housing
D04K01	2.95"(75mm)	5.31"(135mm)	300	Aluminium
D06K11	3.46"(88mm)	7.48"(190mm)	460	Aluminium



Dimmer Compatibility

Dimmer compatibility list indicates those dimmers that have been tested and operate properly under normal conditions.

Dimmer Brand	Model	Dim Range 1 lamp Min Max	Dim Range 10 lamp Min Max	Comment
LEVITON	6631	1.06% 85.64%	2.23% 85.64%	No Flicker
	6161	4.79% 92.02%	5.27% 92.02%	No Flicker
	TTI06	4.79% 88.30%	5.04% 88.30%	No Flicker
	6681	1.60% 98.40%	2.30% 98.40%	No Flicker
	6633	1.17% 95.74%	2.56% 95.74%	No Flicker
	IPI06	2.13% 87.23%	3.56% 87.23%	No Flicker

Dimmer Brand	Model	Dim Range 1 lamp Min Max	Dim Range 10 lamp Min Max	Comment
LUTRON	D-603P	1.60% 78.61%	2.53% 78.61%	No Flicker
	DVCL-153P	4.26% 78.72%	4.80% 78.72%	No Flicker
	MA-600	6.38% 85.11%	6.38% 85.11%	No Flicker
	DV-600P	1.60% 81.38%	1.90% 81.38%	No Flicker

Parameters

Model No.	Base Type	Wattage (W)	Voltage (V)	Power Factor	CRI (Ra)	Lumens (lm)	Beam Angle (°)	CCT* (K)	Housing	Weight (g)	Lifetime L70(hrs)	Dimmable	Certification
D04K01-D	E26/GU24	10	AC120	0.9	80/90	750/650	100	2700~5000	Fit 4"	300	50,000	Yes	UL,ES
D06K21-D	E26/GU24	12	AC120	0.9	80/90	900/820	100	2700~5000	Fit 5"×6"	460	50,000	Yes	UL,ES
D06K11-D	E26/GU24	15	AC120	0.9	80/90	1100/1000	100	2700~5000	Fit 5"×6"	460	50,000	Yes	UL,ES
D06K01-D	E26/GU24	20	AC120	0.9	80/90	1500/1400	100	2700~5000	Fit 5"×6"	460	50,000	Yes	UL,ES

